



Faculty of Manufacturing Engineering

FLEXIBLE LOT SIZE FOR KANBAN SYSTEM TO REDUCE MATERIAL OVERFLOW IN HARD DISC ASSEMBLY PROCESS

Fatma Hermining Astuti

Master of Science in Manufacturing Engineering

2015

**FLEXIBLE LOT SIZE FOR KANBAN SYSTEM
TO REDUCE MATERIAL OVERFLOW
IN HARD DISC ASSEMBLY PROCESS**

FATMA HERMINING ASTUTI

**A thesis submitted
in fulfillment of the requirements for the degree of Master of Science
in Manufacturing Engineering**

Faculty of Manufacturing Engineering

UNIVERSITI TEKNIKAL MALAYSIA MELAKA

2015

DECLARATION

I declare that this thesis entitled “Flexible Lot Size for Kanban System to Reduce Material Overflow in Hard Disc Assembly Process” is the result of my own research except as cited in the references. This thesis has not been accepted for any degree and is not currently submitted in candidature of any other degree.

Signature :

Name : Fatma Hermining Astuti

Date : April, 1st 2015

APPROVAL

I hereby declare that I have read this thesis and in my opinion this thesis is sufficient in terms of scope and quality for the award of Master of Science in Manufacturing Engineering.

Signature :

Supervisor Name : Dr. Zuhriah Ebrahim

Date :

Signature :

Co-Supervisor Name : Prof. Dr. Mohd Razali Muhamad

Date :

DEDICATION

To:

My beloved mother and father

My lovely husband

My beloved sister, brother, niece, and nephew

ABSTRACT

This research was conducted based on a case study at an electronic manufacturing company that produces hard disc. Here, Kitting is the first step in assembly process. It is initiated well before the commencement of actual production to be able to prepare and deliver the material on time. Compound/Kitting section involves the provision of all the materials needed for a particular assembly process from the Warehouse and issuing the materials to the Assembly line. The Compound/Kitting section has been always crowded with high incoming materials (overflow) such that more spaces are needed to allocate the incoming materials. Therefore, the aim of this research is to minimize the overflow of incoming materials at Compound/Kitting section. Thus, three objectives are set: (i) to identify the overflow of incoming material at Compound/Kitting section and its implication to the performance of the subsequent production process, (ii) to analyze the demand changes patterns at production shop floor and its effects to the Compound/Kitting section and Assembly line performances, and (iii) to propose and evaluate the Flexible Lot Size for Kanban System to minimize the overflow of incoming materials. In this regard, Lean Manufacturing tools and techniques such as Value Stream Mapping (VSM) and Kanban system have been adopted to overcome the overflow of incoming materials. The constructed current VSM shows the lack of ordering system and the uncertain changes in demand cause to the overflow of incoming materials. Motivated by these factors, a Flexible Lot Size (FLS) for Kanban System is proposed to resolve the phenomenon. The FLS was modeled using simulation software. It begins by developing the current production simulation model that validated by the historical data of production input and output at Warehouse, Compound/Kitting section and also Assembly line section. In this study, the demand was classified into three categories: low, medium, and high. This research conclude that VSM is an effective tool to map the problems, while the FLS was able to provide the optimum Kanban number and lot size for the case of uncertain demand. In conclusion, a smooth production flow between Warehouse, Compound/Kitting section and Assembly line section can be sustained using the JIT concept “the right quantity at the right time”. In this way, the overflow of incoming materials at Compound/Kitting section has been decreased till 87.3 percent.

ABSTRAK

Kajian ini telah dijalankan berdasarkan satu kajian kes di sebuah syarikat pembuatan elektronik yang menghasilkan cakera keras. Di sini, Kitting adalah langkah pertama dalam proses pemasangan. Ianya dimulakan sebelum bermulanya produksi yang sebenar sehingga dapat menyediakan dan mengedarkan bahan pada masa yang tepat. Seksyen Compound/Kitting melibatkan penyediaan semua bahan yang diperlukan untuk proses pemasangan yang tertentu daripada Gudang dan mengedarkan bahan tersebut kepada Barisan Pemasangan. Seksyen Compound/Kitting sentiasa sesak dengan bahan-bahan yang masuk dalam jumlah yang berlebihan (overflow) di mana lebih banyak ruang yang diperlukan untuk memperuntukkan bahan-bahan yang masuk tersebut. Oleh itu, tujuan kajian ini adalah untuk mengurangkan limpahan bahan masuk di bahagian seksyen Compound/Kitting. Dalam kes ini, tiga objektif telah ditetapkan: (i) untuk mengenal pasti limpahan bahan masuk di seksyen Compound/Kitting dan implikasinya kepada pelaksanaan proses pengeluaran yang berikutnya, (ii) untuk menganalisis corak perubahan permintaan pada produksi shopfloor dan kesannya kepada prestasi di seksyen Compound/Kitting dan Assembly line, dan (iii) untuk mencadangkan dan menilai satu Sistem Kanban dengan Fleksibel Saiz Lot bagi mengurangkan limpahan bahan masuk. Dalam hal ini, alat dan teknik dalam Lean Manufacturing seperti Value Stream Mapping (VSM) dan sistem Kanban telah diterima pakai untuk mengatasi limpahan bahan masuk. VSM semasa yang dibina menunjukkan kekurangan pada sistem dan perubahan yang tidak menentu dalam permintaan menyebabkan limpahan bahan masuk. Didorong oleh faktor-faktor tersebut, Fleksibel Saiz Lot (FLS) untuk Kanban Sistem dicadangkan untuk menyelesaikan fenomena ini. FLS untuk Kanban Sistem dibangunkan dengan menggunakan model simulasi dan disahkan oleh data sejarah input dan output di Gudang, seksyen Compound/Kitting dan juga seksyen Barisan Pemasangan. Dalam kajian ini, permintaan diklasifikasikan kepada tiga kategori iaitu: rendah, sederhana, dan tinggi. Kajian ini menyimpulkan bahawa VSM adalah alat yang berkesan untuk memetakan masalah, manakala FLS mampu menyediakan jumlah Kanban dan saiz lot yang optimum untuk kes permintaan yang tidak menentu. Kesimpulannya, aliran pengeluaran yang lancar antara Gudang, seksyen Compound/Kitting dan juga seksyen Barisan Pemasangan boleh dikekalkan dengan menggunakan konsep JIT iaitu "kuantiti yang betul di masa yang betul". Dengan cara ini, bahan melimpah yang masuk di seksyen Compound/Kitting telah berkurangan sehingga 87.3 peratus.

ACKNOWLEDGEMENTS

Alhamdulillah, Allah Ta'ala has given me a gift to this thesis which may be a religious charity to me personally.

It would not have been possible to write this thesis without the help and support of the kind people around me, to only some of whom it is possible to give particular mention here.

This thesis would not have been possible without valuable help, support, and patience of my honorable supervisors, Dr. Zuhriah Ebrahim and Prof. Dr. Mohd. Razali bin Muhamad.

May Allah Ta'ala reward them with a reply that much better than what all they have done.

I thanks sincerely to my best comrades: Hayati, Herdi, Zaky, Dita, Windi, PPI UTeM and to all colleagues and others who have provided assistance at every occasion of my study.

Finally, I convey my deepest gratitude and sincere love to my blessed parents, Ibu. Marsini and Bapak. Agus Hadi Wahyono; to my beloved husband, Nova Gozalli Kardiyo, my lovely sister and brother Anita Rahmawati and Rosyid Hadi Nugroho; and to my little niece and nephew, Oasis Danada Parama and Guntur Salahudin Isam, for their uncountable love, prayers, and encouragement. Ya Allah, please, I hope you reward them in the world and the hereafter.

TABLE OF CONTENTS

	PAGE
DECLARATION	
DEDICATION	
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENT	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vii
LIST OF FIGURES	ix
LIST OF APPENDICES	xi
LIST OF ABBREVIATIONS	xii
LIST OF PUBLICATIONS	xiii
 CHAPTER	
1. INTRODUCTION	1
1.1 Motivation	1
1.2 Problem Statement	2
1.3 Research Questions	3
1.4 Research Aim and Objectives	3
1.5 Research Scopes and Limitations	4
1.6 Expected Outcome	4
1.7 Research Contributions	5
1.8 Thesis Outline	5
 2. LITERATURE REVIEW	7
2.1 Recent Issues in Electronics Manufacturing Company	7
2.2 Lean Manufacturing	10
2.2.1 Lean Principles	10
2.2.2 Manufacturing Wastes	13
2.2.3 Lean Tools and Techniques	20
2.3 Value Stream Mapping	26
2.3.1 Various Tools in Value Stream Mapping	27
2.3.2 Application of Value Stream Mapping	28
2.3.3 Benefits of Value Stream Mapping	30
2.3.4 Shortcomings of Value Stream Mapping	31
2.4 Kanban System	32
2.4.1 Mechanism of Kanban System	33
2.4.2 The Kanban Number	38
2.4.3 Flexible Kanban System	39
2.4.4 Benefits of Kanban System	41
2.5 Simulation Modeling	42
2.5.1 Simulation Model Application in Lean Manufacturing	43
2.5.2 Benefits of Simulation Model	44
2.6 Summary	45

3.	METHODOLOGY	45
3.1	Introduction	45
3.2	Data Collection	47
3.2.1	Quantitative Data	47
3.2.2	Qualitative Data	49
3.3	Development of Value Stream Mapping	51
3.3.1	Data Collection and Analysis	51
3.3.2	Family Product Selection	53
3.3.3	Material and Information Flow	53
3.3.4	Standard Cycle Time	54
3.3.5	Value Stream Mapping Development	54
3.4	Analysis of the Demand Pattern	55
3.4.1	Data Collection and Analysis	57
3.4.2	Changes of Demand Pattern	57
3.4.3	Effect of Demand Changes Pattern to the Performance of Compound/Kitting section and Assembly Line section	58
3.5	Development of Flexible Lot Size for Kanban System	58
3.5.1	Data Collection and Analysis	60
3.5.2	Development of Current Production System Simulation Model	61
3.5.3	Development of Kanban System Simulation Model	68
3.5.4	Development of Flexible Lot Size for Kanban System Simulation Model	71
3.6	Summary	72
4.	MODEL DEVELOPMENT	73
4.1	Value Stream Mapping Development	73
4.1.1	Current State Value Stream Mapping	74
4.1.2	Future State Value Stream Mapping	77
4.2	Analysis of Demand Changes Pattern	77
4.2.1	Demand Classification	78
4.3	Simulation Model Development	79
4.3.1	Current Production System Simulation Model	79
4.3.2	Kanban System Simulation Model	89
4.3.3	Flexible Lot Size for Kanban System Simulation Model	91
4.4	Summary	94
5.	RESULT AND DISCUSSION	95
5.1	Incoming Materials overflow at Compound/Kitting Section	95
5.1.1	The Nature of Incoming Material Overflow at Compound/Kitting Section	95
5.1.2	The Impact of Incoming Material Overflow at Compound/Kitting Section	98
5.1.3	Discussion	101
5.2	Demand Changes Pattern at the Production Shop floor	102
5.2.1	Effect of Demand Changes Pattern	105
5.2.2	Discussion	107
5.3	The Proposed Flexible Lot Size for Kanban System	108
5.3.1	Current Production System Simulation Model	108
5.3.2	Flexible Lot Size for Kanban System Simulation Model	111
5.4	Summary	119

6.	CONCLUSIONS	120
6.1	Conclusions	120
6.2	Research Contributions	122
6.3	Future Work	122
	REFERENCES	123
	APPENDICES	136

LIST OF TABLES

TABLE	TITLE	PAGE
2.1	Challenges faced by companies in electronic industry	8
2.2	Lean manufacturing tools and techniques	21
2.3	The rules and functions of Kanban system	36
3.1	The list of quantitative and qualitative data	48
3.2	The scope and level of detail of simulation model	66
4.1	Total planned demand for three months historical data	75
4.2	Location capacity	82
4.3	Actual planned demand and production output (Feb 2012 – April 2012) with demand classification	83
4.4	Material lot size	83
4.5	Processing time	84
4.6	Material transfer time	86
4.7	Production output quantity of simulation model for current production system	88
4.8	Optimization input factors	93
4.9	Optimization parameter	93
5.1	Demand range for demand classification process	103
5.2	Actual planned demand and production output (Feb 2012 – April 2012) with demand classification	104

TABLE	TITLE	PAGE
5.3	Optimization process result	114
5.4	Current standard packaging and the lot size optimization result	116
5.5	Proposed alternative standard packaging of MBA, MEDIA and HAS using FLS for Kanban system	116
5.6	WIP inventory in current system versus FLS for Kanban system	118

LIST OF FIGURES

TABLE	TITLE	PAGE
2.1	Five principles for achieving lean enterprise	11
2.2	Schematic diagram of single card Kanban system	34
2.3	Schematic diagram of two card Kanban system	36
3.1	Flow of activities in the study	46
3.2	Process flow of developing the Value Stream Mapping (Phase 1)	52
3.3	Process flow of identifying the demand pattern (Phase 2)	56
3.4	Process flow of developing the Flexible Kanban System (Phase 3)	59
3.5	A framework of conceptual model	62
3.6	Input and Output variables for simulation model	64
3.7	A schematic diagram of Kanban system	70
4.1	Material and information flow of T product family from Warehouse - Compound/Kitting section – Assembly line section	75
4.2	Material / product flow for simulation of current production system	80
4.3	Material / product flow for simulation of Kanban system	90
5.1	Current state VSM for T family product	96
5.2	Future state VSM for T family product	100
5.3	Demand pattern and production performances	106
5.4	Snap shot of simulation model of current production system	109
5.5	Normality test of validation result	110
5.6	One-sample T test of validation result	112

TABLE	TITLE	PAGE
5.7	Two-sample T test result for determining the replication number	112
5.8	Comparison of planned demand and production output of actual system, simulation model, and FLS for Kanban system	118

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Gantt chart of research activities	130
B	Value Stream Mapping symbol	131
C	Three months historical data of planned demand per shift and production output	135
D	Detail Flexible Lot Size for Kanban System optimization result	136

LIST OF ABBREVIATIONS

CT	-	Cycle Time
DES	-	Discrete Event Simulation
eVSM	-	electronic Value Stream Mapping
FKS	-	Flexible Kanban System
FLS	-	Flexible Lot Size
HDA	-	Hard Disc Assembly
JIT	-	Just In Time
LM	-	Lean Manufacturing
MCS	-	Material Control System
NVA	-	Non Value Added
POK	-	Production Order Kanban
PPC	-	Production Planning and Control
QFD	-	Quality Function Deployment
SimVSM	-	Simulation based Value Stream Mapping
SMED	-	Single Minute Exchange of Dies
TKS	-	Traditional Kanban System
TPM	-	Total Productive Maintenance
VA	-	Value Added
Vs	-	Versus
VSM	-	Value Stream Mapping
WIP	-	Work In Process
WK	-	Withdrawal Kanban

LIST OF PUBLICATION

Astuti, F.H., Ebrahim, Z., Muhamad, M.R., 2012. Minimizing Overflow of Incoming Materials at Compound/Kitting Section Using Lean Manufacturing Techniques: A Case study at Electronic Manufacturing Company., *International Conference on Design and Concurrent Engineering (iDECON)*. 15th – 16th Oct. Melaka, Malaysia.

CHAPTER 1

INTRODUCTION

1.1 Motivation

Presently, many companies are focusing their effort in implementing the philosophy “*today has to be better than yesterday*” towards achieving higher business efficiency, effectiveness and productivity for their respective companies (Saleh et al., 2012). In general, manufacturing companies have problems in their operation site or shop floor. These problems can be unique where it is specific to a company or general problems such as high waste, low utilisation, high inventory, and over production. As organizations have struggled to remain survive and achieve economic sustainability, manufacturing company must always try to minimize their problems from time to time and improve their productivity.

According to Gershwin (2000) a manufacturing system is a set of machines, transportation elements, computers, storage buffers and other items that are used together for manufacturing. People are also part of the system. Alternate terms of manufacturing system are factory, production system and fabrication facility. Subsets of manufacturing systems, which are themselves systems, are sometimes called cells, work centers or work stations. The problems in manufacturing system, such as excess inventories, long lead times and uncertain delivery dates are caused by randomness and lack of synchronization. In this regard, there are two possible solutions: reduce the randomness (due to machine failures, engineering changes, customer demand and so on) and reasons for the lack of synchronization (costly set-up changes, large batch machines and others) or respond to

them in a way that limits their disruptive effects. Both responses are valid, but they can be, in practice polar opposites.

These problems can be addressed by performing some analysis to their current manufacturing approaches. Many have embraced Lean Manufacturing (LM) as a tool for continuous productivity improvement. LM is a systematic removal of waste by all members of the organization from all areas of the value stream. The value stream is defined as all activities that contribute to the transformation of raw material to end product including design, order taking, and physical manufacture (Womack et al., 1996). There are a number of benefits of LM implementation such as inventory and lead time reduction, quality improvement, and also flexibility enhancement. The practices of LM include 5 S, Kaizen, quick changeovers, Value Stream Mapping (VSM), and Kanban.

In this research, analysis will be done to evaluate current manufacturing approaches of a hard disc manufacturing company in Malaysia. Appropriate LM techniques will be used to identify and reduce or eliminate the apparent waste in their production system. In this way, the productivity can be improved.

1.2 Problem Statement

For hard disc assembly process in the company, different components are delivered from the suppliers arrive at the factory by truck. The components are unloaded into the warehouse area. From the warehouse, trolleys set off according to a schedule from the planner, delivering the components to Compound section and collecting the empty trolleys in the Compound section, then bring back to the warehouse and refilled for the next delivery. In this regard, Compound/Kitting section performs as an intermediate storage that collects the materials supplied directly from Warehouse and issues the materials to the next Assembly lines section. However, it was found that the Compound/Kitting section has a problem of overflow of incoming materials. It is always crowded with high incoming

materials even though the materials are pulled out almost every hour. As a result, 75% of the spaces in the Compound/Kitting section have to be used to store the excess material.

1.3 Research Questions

Based on the problems mentioned above, the main research questions of this study are as follows:

- i. What is the current status of material flow in Warehouse, Compound/Kitting section and Assembly line section (i.e. current production lead time)?
- ii. Do the demand changes in production shop floor affect the Compound/Kitting and Assembly line performance (i.e inventory level, actual production output quantity)?
- iii. How to minimize the overflow of incoming materials in Compound/Kitting section, that caused by the gap between actual production output and planned demand quantity?

1.4 Research Aim and Objectives

The aim of this research is to minimize the overflow of incoming materials. In the mean time, a smooth material flow with a very minimum level of WIP inventory at the Compound/Kitting section can be achieved. Thus, the objectives of this research are:

- i. To identify the overflow of incoming material at Compound/Kiting section and its implication on the performance of the subsequent production process.
- ii. To analyze the changing demand patterns of the production shop floor and its effects on the Compound/Kiting section and assembly line performance.
- iii. To propose and evaluate the Flexible Lot Size for Kanban System to minimize the overflow of incoming materials at Compound/Kitting section.

1.5 Research Scopes and Limitation

This research is based on a case study at a hard disc manufacturing company located in Malaysia. The study focuses on the high WIP of incoming materials at Compound/Kitting section. In this case, the concept of ‘continuous flow’ of Lean Thinking is adopted to solve this high WIP of incoming materials. Appropriate Lean tools and techniques such as Value Stream Mapping (VSM) and Kanban system will be applied to the production system at Compound/Kitting section.

This study selects only one product family, that is the T product family as it comprises 87% of the customer demand. Thus, class A inventory items of product T family will be studied as it presents high usage in the hard disc assembly process. The class A items are MBA, MEDIA, and HAS. These items contribute to high inventory cost in term of high WIP that consume large space at Compound/Kitting section.

1.6 Expected Outcome

The expected outcome of the study is the minimization of incoming material overflow at Compound/Kitting section. In addition, through the VSM tool, production wastes at every sub-process in the Compound/Kitting section could be identified and later eliminated. The proposed Flexible Lot Size for Kanban System would be able to provide a smooth material flow between Warehouse, Compound/Kitting section and Assembly line section with minimum WIP inventory.

1.7 Research Contributions

This research contributes to new knowledge for hard disc assembly process in the aspects of:

- i. Clarification of the gaps between the planned demand and actual production output.
- ii. Identification of the effects of changes in demand volume to the Compound/Kitting performances.
- iii. Development of Flexible Lot Size for Kanban System that will be able to minimise the overflow of incoming materials at Compound/Kitting section.

1.8 Thesis Outline

This thesis is organized in six chapters. The topics addressed in each chapter are as follows:

Chapter 1 presents background related to the subject of this study which is electronic manufacturing company. The problem statements are given followed by the aim and objectives of the study. The chapter provides a focus and limitation in order to define the scope and to outline the study. The expected result and benefits of this study are also explained in this chapter.

Chapter 2 the literature review provides an extensive review of the existing literature on the challenges faced by electronic manufacturing company, LM system, and simulation study. The problems faced by electronic manufacturing company are reviewed in the early stage. The chapter then seeks to identify the philosophies and core principles of LM followed by the different tools, approaches and techniques of LM. Next, the theories of simulation derived from the literature review, as an aid tool in adopting the LM system to solve the company's problem.

Chapter 3 consists of explanation of the research methodology used in this thesis. The method is mentioned and reasoned as well as the strategies exploited in this study. In addition, the required data and details in data collection are also mentioned in this subchapter.

Chapter 4 explains the development of FLS model for Kanban system. In this chapter, the key components and the mechanism to develop the models are described in detail.

Chapter 5 presents the result that was acquired through the research methodology and model development explained in previous chapter. This chapter also provides the analysis and discussion of the result gained.

Chapter 6 In this chapter, summary of research findings are presented and the answer to the research objectives is clarified. Moreover, the direction for future research is given in the last subchapter.